



Technical specification – e-Heater

Note: The specifications are subject to change without notices.

28410-03 e-Heater 1000 • 28420-03 e-Heater 2000		
Product	28410-03 e-Heater 1000	28420-03 e-Heater 2000
Heat output	750W @ +25C 1050W @ -25C	1500W @ +25C 2100W @ -25C
Fan Cool/Recirculate	YES	YES
PTC elements	2	4
Nominal heat Output Temperature	+55C @ -25C ambient +90C @ +25C ambient	+90C @ +25C ambient +90C @ +25C ambient
Operating temperature	-40C - +85C	-40C - +85C
Voltage (Nominal)	12V	12V
Operating Voltage	11-14.5V	11-14.5V
Current Continuous	65A Continuous 88A Continuous	130A Continuous 175A Continuous
Current Inrush	115A	230A
Communication To/From Modul-Connect	CAN 1 (MOLEX Pin 8 &16 + Pin 13 GND)	CAN 1 (MOLEX Pin 8 &16 + Pin 13 GND)
Internal battery guard	10V	10V
Dimensions (LWH) (mm)	320 x 315 x 140	320 x 315 x 140
Weight	5 kg	6,35 kg
Warrenty	3 year	3 year
Certifications	R10, CE UKCA	R10, CE UKCA